

Switch Bank #1

Switch	Function	ON	OFF
1	Odd/Even	Odd	Even
2	Parity	Without	With
3	Data bits	8	7
4	Protocols	Ready/Busy	X-ON/X-OFF
5	Test select	Circuit	Monitor
6	Mode select	Print	Testing
7	Busy line	SW1-7 SW1-8 ON ON	SELECTION DTR (-) Pin 20
8	selection	ON OFF OFF ON OFF OFF	RTS (-) Pin 4 SSD (-) Pin 11 SSD (+) Pin 11

Switch Bank #2

Switch	Function	SW2-1	SW2-2	SW2-3	SPEED
1	baud rate	ON	ON	ON	19,200
2	selection	OFF	ON	ON	9,600
3		ON	OFF	ON	4,800
		OFF	OFF	ON	2,400
		ON	ON	OFF	1,200
		OFF	ON	OFF	600
		ON	OF	OFF	300
		OFF	OFF	OFF	110
			ON		OFF
4	DSR Input signal	ON	ON	ON	Inactive
5	Buffer threshold	32 bytes	32 bytes	32 bytes	256 bytes
6	Busy signal timing	200ms (min.)	200ms (mins.)	200ms (min.)	1 second (max)
7	Not used				
8	Not Used				